

A FINITE ELEMENT APPLICATION OF THE HELLINGER-REISSNER VARIATIONAL THEOREM*

Robert S. Dunham**

Karl S. Pister***

University of California, Berkeley

The Hellinger-Reissner Variational Theorem of linear elastostatics is used to construct a Finite Element Method of solution for boundary value problems in generalized plane stress. A "stiffness" matrix is derived for the case where stress and displacement fields are linear at the element level. Two example problems are included.

* This paper was partially supported by the Army Research Office, Durham, North Carolina and the Naval Ordnance Test Station, China Lake, California.

** Graduate Student in Civil Engineering.

*** Professor of Civil Engineering.

Report Documentation Page				Form Approved OMB No. 0704-0188	
Public reporting burden for the collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to a penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number.					
1. REPORT DATE OCT 1968		2. REPORT TYPE		3. DATES COVERED 00-00-1968 to 00-00-1968	
4. TITLE AND SUBTITLE A Finite Element Application of the Hellinger-Reissner Variational Theorem				5a. CONTRACT NUMBER	
				5b. GRANT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
6. AUTHOR(S)				5d. PROJECT NUMBER	
				5e. TASK NUMBER	
				5f. WORK UNIT NUMBER	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Air Force Flight Dynamics Laboratory, Wright Patterson AFB, OH, 45433				8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)	
12. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited					
13. SUPPLEMENTARY NOTES See also AD0703685, Proceedings of the Conference on Matrix Methods in Structural Mechanics (2nd) Held at Wright-Patterson Air Force Base, Ohio, on 15-17 October 1968.					
14. ABSTRACT					
15. SUBJECT TERMS					
16. SECURITY CLASSIFICATION OF:			17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES 18	19a. NAME OF RESPONSIBLE PERSON
a. REPORT unclassified	b. ABSTRACT unclassified	c. THIS PAGE unclassified			

NOMENCLATURE

$a, \{a\}$	generalized coordinates for displacements
α_{ij}	coefficient of thermal expansion tensor
$\{a_T\}$	thermal expansion vector
$b, \{b\}$	generalized coordinates for stress
$C_{ijkl}, \{C\}$	strain-stress constitutive tensor
∇	gradient operator
δ	variation symbol
$f_i, \{f\}$	body force per unit volume
$\bar{p}_i, \{\bar{p}\}$	prescribed traction on S
R	region occupied by the solid body
$[S]$	stiffness matrix
S_τ	surface of prescribed stresses
S_u	surface of prescribed displacements
T	temperature above a reference temperature
$\tau_{ij}, \{\tau\}$	stress tensor
$[\Phi_\tau]$	coordinate functions for stress
$u_i, \{u\}$	displacement vector
$\bar{u}_i, \{\bar{u}\}$	prescribed displacement on S_u
$[\Phi_u]$	coordinate functions for displacement
V	Hellinger-Reissner functional
W	complementary energy density

SECTION I

INTRODUCTION

A method often used for the solution of initial-boundary value problems in structural mechanics has been the Finite Element Method (References 1, and 2). Many applications of the Finite Element Method in linear elastostatics have been derived from the Theorem of Minimum Potential Energy or its equivalent, the Principle of Virtual Work (Displacements). Consequently, the set of primary field variables is the displacement field; strains and stresses are then expressed as functions of the displacements through the field equations.

It has been assumed that the Finite Element Method yields displacements and stresses which converge as the mesh size is decreased (References 3, 4, and 5). Smooth convergence of the displacement field has been widely reported for many applications (Reference 2 a), some violating certain of the compatibility conditions (Reference 1 a). On the other hand, smooth convergence of the stress field has not always been observed; poor convergence and spatial oscillations are found (Reference 6). Several authors have given stress "averaging" techniques (References 7 and 8). For many engineering purposes it must be recognized that a knowledge of the stress distribution even in localized regions, is the desired result and the displacements are of secondary interest.

Some of these difficulties can be circumvented by mesh resolution and adoption of averaging techniques mentioned above in localized regions with high gradients. However, for some problems this is impossible or impracticable and other alternatives must be sought. One alternative is to employ a higher order displacement expansion. Investigators have pursued this approach with encouraging results (Reference 9 and 10); however, the stress vector remains discontinuous over contiguous element interfaces, giving a stress distribution with a histogram appearance.

Another approach is to obtain the stress directly as a primary variable through an application of the Theorem of Minimum Complementary Energy. Investigators have had limited success with the method, one difficulty being to establish a stress distribution identically satisfying the equilibrium equations and expressible in terms of a convenient set of global generalized coordinates. At present the method has not been applied with the same degree of generality as the displacement method (References 2b, 11, 12 and 13). It is surprising that applications of mixed variational theorems have not been explored in this regard since they offer the generality of the displacement method and retain the stress field as a primary

variable. To this end the present paper introduces a Finite Element application of the Hellinger-Reissner Variational Theorem.

It is shown that expansions for the displacement and stress fields can be made independently in Finite Element analyses and that continuity of the stress vector can be maintained across contiguous element interfaces. Stresses from a mixed variational theorem are shown to be improved over those of comparable displacement models. The limitation principle (Reference 2b) is discussed in this connection and is shown to limit the scope of mixed variational theorems.

A stiffness matrix for plane and axisymmetric solids is discussed and several examples are presented with comparisons made to a frequently used displacement model (Reference 17).

SECTION II

HELLINGER-REISSNER THEOREM

The functional in the theorem is expressed in terms of the displacement and stress field* (Reference 14)

$$V(u, \tau) = \int_R [\tau_{ij} u_{(i, j)} - W(\tau) - f_i u_i] dv - \int_{S_\tau} \bar{p}_i u_i da - \int_{S_u} n_j \tau_{ji} (u_i - \bar{u}_i) da \quad (1)$$

where

$$W(\tau) = \tau_{ij} \left(\frac{1}{2} C_{ijkl} \tau_{kl} + \alpha_{ij} \tau \right) \quad (2)$$

The theorem asserts that of all admissible** displacement and stress states, those states that satisfy the stress equations of equilibrium, the strain stress equations and the boundary conditions render the functional stationary

$$\delta V(u, \tau) = 0 \quad (3)$$

Unlike the minimum principles the stationary value cannot be shown to be an extremum value of the functional (Reference 14).

The form of the functional is such that separate expansions are possible without the restrictions necessary in the minimum principles. The stress field need not satisfy the equilibrium or stress-strain-displacement equations in R , nor need either the displacement or stress fields satisfy the prescribed boundary conditions. The Euler Equations are the stress equations of equilibrium, the strain-stress law and the boundary conditions. Since the stationary value of the functional contains the constitutive equation as an Euler Equation, the stress field obtained through the stress-strain-displacement relations may not agree with the stress field given by the stationary value.

* Standard tensor notation is used and a cartesian reference frame is assumed; comma denotes differentiation, repeated indices are summed, and parentheses denote the symmetric part of a tensor. Interpretation of the symbols is given in the Appendix.

** Admissibility and convergence questions are beyond the scope of the present work (Reference 15).

If independent expansions are used for both fields, where components of the displacement and stress fields are adjoined across contiguous element boundaries using a system of common displacement and stress nodal points, then a direct solution for the primary variables should differ from corresponding applications of the minimum principles. However, the limitation principle requires that the stress variables be left free (Reference 2b). The notion of connectivity in the stress variables is central to this concept. To illustrate this, consider the following*:

$$u_i = \phi_i^n(x_p) a_n \quad (4)$$

$$\tau_{ij} = \psi_{ij}^n(x_p) b_n \quad (5)$$

where the a's and b's are the generalized coordinates for displacement and stress, respectively. Suppose there exists a set of scalars β_n^m such that

$$\psi_{ij}^n(x_p) \beta_n^m = c_{ijkl} \phi_{kl}^m(x_p) \quad (6)$$

Then if there is no interelement connectivity in the stress variables, Euler Equation of the functional is identically satisfied. The stationary value yields, in part,

$$\frac{\partial V}{\partial \tau_{ij}} = 0 \Rightarrow \frac{\partial V}{\partial b_n} = 0 \quad (7)$$

using Equation 4 in Equation 1, and assuming

$$\begin{aligned} u_i &= \bar{u}_i \quad \text{on } S_U \\ f_i &= 0 \quad \text{in } R \\ T &= 0 \end{aligned} \quad (8)$$

Equation 7 becomes

$$\int_R [\phi_{i,j}^n a_n - c_{ijkl} \psi_{kl}^n b_n] \psi_{ij}^m \delta b_m dv = 0 \quad (9)$$

from Equation 6, if

$$b_n = \beta_n^m a_m$$

then

$$(\phi_{i,j}^m - c_{ijkl} \psi_{kl}^n \beta_n^m) a_m = 0 \quad (10)$$

* The superscripts refer to generalized coordinates and are treated as ordinary indices.

Equations 6 and 10 imply that the stress is computed from the stress-strain-displacement relations and

$$\tau_{ij} = C_{ijkl}^{-1} u_{k,l} \quad (11)$$

thus

$$\tau_{ij} u_{(i,j)} - W(\tau) = \frac{1}{2} u_{i,j} C_{ijkl}^{-1} u_{k,l} \quad (12)$$

in which case Equation 12 and Equation 8 imply the functional in Equation 1 can be reduced to

$$V(u) = \int_R \frac{1}{2} u_{i,j} C_{ijkl}^{-1} u_{k,l} dv - \int_{S_\tau} \bar{p}_i u_i da. \quad (13)$$

Equation 13 is the functional in the Theorem of Minimum Potential Energy.

The above is a demonstration of the limitation principle which is seen to hold in the restrictive case where the stress variables are not connected from element to element.

SECTION III

A FINITE ELEMENT MODEL

Following the approach in (Reference 16) a linear expansion is taken for both the stress and displacement, and a system of generalized coordinates is established at the vertices of a triangular element for a plane stress or axisymmetric solid. Matrix notation is employed for convenience. Displacement boundary conditions are to be satisfied in the usual fashion. Derivation of an element stiffness matrix for a two-dimensional plane stress solid is given for a linear triangular element. A more complete exposition for both plane and axisymmetric solids is given in (Reference 16).

For the stated application, the functional in Equation 1 can be expressed

$$V(u, \tau) = \int_R (\langle \tau \rangle \{ \nabla u \} - W(\tau) - \langle u \rangle \{ f \}) dv - \int_{S_\tau} \langle u \rangle \{ \bar{p} \} d\sigma \quad (14)$$

where

$$W(\tau) = \langle \tau \rangle \left(\frac{1}{2} [C] \{ \tau \} + \{ \alpha \tau \} \right) \quad (15)$$

and the brackets $\langle \rangle$ and $\{ \}$ are used to represent row and column matrices, respectively. The coordinate functions expansions are

$$\begin{aligned} \{ u \} &= [\Phi_u] \{ a \} \\ \{ \tau \} &= [\Phi_\tau] \{ b \} \end{aligned} \quad (16)$$

where

$$\begin{bmatrix} u \\ v \end{bmatrix} = \begin{bmatrix} \langle \phi \rangle & \langle 0 \rangle \\ \langle 0 \rangle & \langle \phi \rangle \end{bmatrix} \begin{bmatrix} a_1 \\ \vdots \\ a_6 \end{bmatrix} \quad (17)$$

$$\begin{bmatrix} \tau_{xx} \\ \tau_{yy} \\ \tau_{xy} \end{bmatrix} = \begin{bmatrix} \langle \phi \rangle & \langle 0 \rangle & \langle 0 \rangle \\ \langle 0 \rangle & \langle \phi \rangle & \langle 0 \rangle \\ \langle 0 \rangle & \langle 0 \rangle & \langle \phi \rangle \end{bmatrix} \begin{bmatrix} b_1 \\ \vdots \\ b_9 \end{bmatrix} \quad (18)$$

$$\langle \phi \rangle = \langle 1, x, y \rangle \quad (19)$$

and the displacement gradients are

$$\{ \nabla u \} = [\Phi'_u] \{ a \} \quad (20)$$

The generalized coordinates are expressed in terms of the values of the physical components of the displacement and stress fields at the element vertices, (Figure 1)

$$\begin{aligned}\{u_o\} &= [\Phi_{u_o}] \{a\} \\ \{\tau_o\} &= [\Phi_{\tau_o}] \{b\}\end{aligned}\tag{21}$$

where

$$\begin{aligned}\langle u_o \rangle &= \langle u_i, u_j, u_k, v_i, v_j, v_k \rangle \\ \langle \tau_o \rangle &= \langle \tau_{xx_i}, \tau_{xx_j}, \tau_{xx_k}, \tau_{yy_i}, \dots, \tau_{xy_k} \rangle\end{aligned}\tag{22}$$

$$[\Phi_{u_o}] = \begin{bmatrix} [\phi_o] & 0 \\ 0 & [\phi_o] \end{bmatrix}\tag{23}$$

$$[\Phi_{\tau_o}] = \begin{bmatrix} [\phi_o] & 0 & 0 \\ 0 & [\phi_o] & 0 \\ 0 & 0 & [\phi_o] \end{bmatrix}\tag{24}$$

$$[\phi_o] = \begin{bmatrix} 1 & x_i & y_i \\ 1 & x_j & y_j \\ 1 & x_k & y_k \end{bmatrix}\tag{25}$$

Thus

$$\begin{aligned}\{a\} &= [\Phi_{u_o}^{-1}] \{u_o\} \\ \{b\} &= [\Phi_{\tau_o}^{-1}] \{\tau_o\}\end{aligned}\tag{26}$$

and

$$\begin{aligned}\{u\} &= [\Phi_u] [\Phi_{u_o}^{-1}] \{u_o\} \\ \{\tau\} &= [\Phi_\tau] [\Phi_{\tau_o}^{-1}] \{\tau_o\} \\ \{\nabla u\} &= [\Phi'_u] [\Phi_{u_o}^{-1}] \{u_o\}\end{aligned}\tag{27}$$

The functional becomes

$$v = \frac{1}{2} \langle \tau_o \rangle [S_{\tau\tau}] \{ \tau_o \} + \langle \tau_o \rangle [S_{\tau u}] \{ u_o \} - \langle \tau_o \rangle \{ F_\tau \} - \langle u_o \rangle \{ F_u \} \quad (28)$$

where

$$\begin{aligned} [S_{\tau\tau}] &= -[\Phi_{\tau_o}^{-1}]^T \left(\int_R [\Phi_\tau]^T [C] [\Phi_\tau] dv \right) [\Phi_{\tau_o}^{-1}] \\ [S_{\tau u}] &= [\Phi_{\tau_o}^{-1}]^T \left(\int_R [\Phi_\tau]^T [\Phi'_u] dv \right) [\Phi_{u_o}^{-1}] \\ \{ F_\tau \} &= [\Phi_{\tau_o}^{-1}]^T \left(\int_R [\Phi_\tau]^T \{ \alpha \tau \} dv \right) \\ \{ F_u \} &= [\Phi_{u_o}^{-1}]^T \left(\int_R [\Phi_u]^T \{ f \} dv + \int_{S_\tau} [\Phi_u]^T \{ \bar{p} \} d\sigma \right) \end{aligned} \quad (29)$$

The stationary value yields the governing equations

$$\begin{bmatrix} S_{\tau\tau} & S_{\tau u} \\ S_{\tau u}^T & 0 \end{bmatrix} \begin{bmatrix} \tau_o \\ u_o \end{bmatrix} = \begin{bmatrix} F_\tau \\ F_u \end{bmatrix} \quad (30)$$

The linear triangular element is used to form the quadrilateral element shown in Figure 1. Condensation is then performed on the stiffness matrix in order to reduce the bandwidth of the governing Equations 9 and 17. However, in the case of the present mixed model this cannot be effected directly due to a singularity found during the Gaussian elimination. What is done




Figure 1. Four-Triangle Quadrilateral

is to constrain the displacements at the center node to be the average of the four exterior nodes

$$\begin{aligned} u_5 &= \frac{1}{4} (u_1 + u_2 + u_3 + u_4) \\ v_5 &= \frac{1}{4} (v_1 + v_2 + v_3 + v_4) \end{aligned} \quad (31)$$

or

$$\{u_o\} = [\Psi] \{u_o\}_c \quad (32)$$

where

$$[\Psi] = \begin{bmatrix} [\Psi] & [0] \\ [0] & [\Psi] \end{bmatrix} \quad (33)$$

and

$$[\Psi] = \begin{bmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & 1 \\ \frac{1}{4} & \frac{1}{4} & \frac{1}{4} & \frac{1}{4} \end{bmatrix} \quad (34)$$

The constrained stiffness matrix becomes

$$[S_{ru}]_c = [S_{ru}][\Psi] \quad (35)$$

Standard techniques are used to solve the resulting system of linear algebraic Equation 30. Although Equation 30 is not a positive definite system, no difficulty is encountered in Gaussian elimination if nodal point stress are eliminated before the displacements.

SECTION IV

EXAMPLES

To illustrate the method, two example problems are given with direct solutions obtained using the mixed model and a comparable displacement model Reference 17.

A boundary value problem with an applied linear stress distribution is shown in Figure 2. The problem is equivalent to combined extension and flexure in elementary beam theory. The two-dimensional plane stress solution is

$$\begin{aligned}\tau_{xx} &= y, \quad \tau_{xy} = \tau_{yy} = \tau_{zz} = 0 \\ \epsilon_{xx} &= \frac{y}{E}, \quad \epsilon_{yy} = -\frac{\nu y}{E}, \quad \epsilon_{xy} = 0 \\ u(x, y) &= \frac{xy}{E}, \quad v(x, y) = -\frac{1}{2E} (x^2 + \nu y^2)\end{aligned}\tag{36}$$

The linear stress distribution is contained within the expansion for the stress field in Equation 16, but the displacement field is parabolic.

Figure 2 shows a plot of the stress field along the top fiber of the beam and through the depth at the edge of applied traction. The mixed model gives accurate values for the stress field including those points on the boundary. The displacement model gives values for the stress only at the element centroid. The mixed model also predicts the deformed profile with considerable accuracy.

Figure 3 illustrates a finite length hollow cylinder, fixed at the outer radius and acted upon by an internal pressure. The geometry and physical properties are

$$\begin{aligned}a &= 4, \quad b = 6, \quad \ell = 5.5 \\ \frac{p}{E} &= 1, \quad \nu = 0.4\end{aligned}\tag{37}$$

A plot of the normal stress distribution along the fixed boundary is given in Figure 3 for the two Finite Element models. The stress singularity is seen to be more severe in the mixed model, the displacement model suppressing much of the gradient in the vicinity of the singularity.




Figure 2. A Linear Stress Problem




Figure 3. Pressurized Finite Cylinder

SECTION V

CONCLUSIONS

For the examples considered the present application of the Hellinger-Reissner Theorem gives a more accurate field description of both displacement and stress than do existing applications of displacement models. The mixed model yields solutions in which all components of the stress tensor are continuous from element to element, eliminating the histogram distribution often found in displacement models. The displacement vector obtained from the mixed model is considerably more accurate than that given by comparable displacement models. Results for the stress field are superior, but tend to be dependent on material properties and mesh configuration. In part, this can be attributed to identically satisfying the displacement boundary conditions. Since the stress distribution is the desired result, it would be advantageous to bias the model in this direction. An alternate form of the functional which accomplishes this is currently being studied.*

The mixed model is shown to be highly effective in capturing steep stress or displacement gradients that can occur near singularities in boundary value problems. These are often not predicted by displacement models. The mixed model is most effectively used for this class of problems since an excess of generalized coordinates can require considerable computational effort for a general problem.

The present effort should be regarded as introductory, and considerable additional research is indicated. Alternate forms should be considered. The number of generalized coordinates should be reduced by employing other coordinate functions and element configurations. Herrmann has shown that this can be done for plate bending (Reference 1b), and Prager (Reference 18), has extended and systematized the relevant principles. What has been clearly demonstrated here is that Finite Element Methods can be successfully used with mixed variational theorems for direct solutions to boundary value problems in mechanics.

*This form has been suggested by S. Pawsey in private communications.

SECTION VI

REFERENCES

1. "Matrix Methods in Structural Mechanics," Proceedings of the Conference held at Wright-Patterson Air Force Base, Ohio, 1966.
 - a. Clough, R. W. and Tocher, J. L., "Finite Element Stiffness Matrices for Analysis of Plate Bending."
 - b. Herrmann, L. R., "A Bending Analysis for Plates."
2. Zienkiewicz, O. C. and Holister, G. S., Stress Analysis, John Wiley, 1965.
 - a. Clough, R. W., "The Finite Element Method in Structural Mechanics," Chapter 7.
 - b. de Veubeke, B. F., "Displacement and Equilibrium Models in the Finite Element Method," Chapter 9.
3. Melosh, R. J., "Basis for Derivation of Matrices for the Direct Stiffness Method," AIAA Jour., 1/7, 1963.
4. Felippa, C. A. and Clough, R. W., "The Finite Element Method in Solid Mechanics," Symposium of the American Mathematical Society, Durham, North Carolina, 1968.
5. Johnson, M. W., and McLay, R. W., "Convergence of the Finite Element Method in the Theory of Elasticity," JAM, 35/2, 1968.
6. Anderson, J. M., and Christiansen, H. N., "Behavior of the Finite Element Stiffness Method for Nearly Incompressible Materials," Proceedings of the 6th Meeting of the Mechanical Behavior Working Group, ICRPG, Jet Propulsion Lab, Pasadena, California, 1967.
7. Utku, S., "Best Fit Stress Computation in Displacement Methods," EMD Speciality Conference, North Carolina State University, 1967.
8. Becker, E. H. and Brisbane, J. J., "Application of the Finite Element Method to Stress Analysis of Solid Rocket Propellant Grains," Rohm and Haas Report S-76, Huntsville, Alabama, 1965.

9. Felippa, C. A., A Refined Finite Element Analysis of Linear and Non-Linear Two-Dimensional Structures, Structural Engineering Laboratory Report 66-22, University of California, Berkeley, 1966.
10. Tocher, J. L. and Hartz, B. J., "Higher Order Finite Element for Plane Stress," Jour. Engin. Mech. Div., ASCE, 93/4, 1967.
11. Shubinski, R. P., Bounds on the Generalized Plane Stress Problem by a Method Related to the Synge Hypercircle, Ph.D. Dissertation, University of California, Berkeley, 1965.
12. Hartz, B. J. and Watwood, V. B., Equilibrium Stress Field Models in Finite Elements, University of Washington Report, Seattle, 1967. (To be published)
13. Chan, S. T. K., Investigations of Finite Element Procedures based on the Theorem of Minimum Complementary Energy, M. S. Thesis, University of California, Davis, 1967. (To be published with L. R. Herrmann)
14. Reissner, E., "On A Variational Theorem in Elasticity," Journal of Mathematical Physics, 29/1, 1950.
15. Prager, W., "Variational Principles of Linear Elastostatics for Discontinuous Displacements, Strains and Stresses," Recent Progress in Applied Mechanics Odqvist Volume, Almquist and Wiksell, Stockholm, 1967.
16. Dunham, R. S., Stationary Principles Applied to a Class of Linear and Nonlinear Boundary Value Problems in Solid Mechanics, Ph.D. Dissertation, University of California, Berkeley, 1968.
17. Goudreau, G. L., Nickell, R. E., and Dunham, R. S., Plane and Axisymmetric Finite Element Analysis of Locally Orthotropic Elastic Solids and Orthotropic Shells, Structural Engineering Laboratory Report 67-15, University of California, Berkeley, 1967.
18. Prager, W., Variational Principles for Elastic Plates with relaxed Continuity Requirements, Technical Report No. 16, University of California, San Diego, 1968.

